

AVKOPACK® 1101S



CHARACTERISTICS

Gland packing braided by expanded PTFE yarn FINITEXT Pe 100

Application

AVKOPACK® 1101 S is braided from yarn with extreme tensile strength and it is better and more resistant than conventional PTFE packing. Special high quality components, which are added in the packing, combined with low coefficient of friction of Teflon improve heat conductivity and made this packing suitable for the sealing of high speed rotation pumps.

AVKOPACK® 1101 S is characterized with high chemical resistance. The packing is suitable both for acids and for bases. These properties, combined with high purity of the used yarn define its application in production processes with high purity of the working fluid.

The fields of usage are sealing installations and equipment in the chemical, pharmaceutical, oil refining and food processing industries, and in the chemical departments of the power supplying industry.

Advantages

The packing has very low shrinkage and does not lose volume, which is a guarantee for a high degree hermetically sealed compound. AVKOPACK® 1101 S has micro porous structure, which holds important lubricants.

Technical parameters

Working temperature:	-200°C / +280°C
Working pressure:	
- for rotary - pumps:	30 bar
- for piston - pumps:	30 bar
- for armature:	250 bar
pH:	0 – 14
V:	15 m/s
Standard dimensions:	from 4 x 4 mm to 25 x 25 mm
	*Other sizes on request

Quality Control

The whole production process is supervised in accordance with the Quality System ISO 9001, ISO 14001, OHSAS 18001.

Human hazardous

Not registered.